

ULTRA-COMPACT 5 W 2 m FM HANDHELD TRANSCEIVER

FT-250R/E*

*E for European Version

Compact Field Radio with

Top Mounted LCD and Loud Audio



- Compact Design with Top mounted LCD Display
- 5 Watts of Stable RF Power with Minimum Components for Reliability
- 700 mW of Loud Audio for outside field environments
- 200 Memory Channels for serious users
- Yaesu Exclusive Power Saving Circuit Design Guarantees Longer Operating time
- Hands Free Operation with Optional VC-25 VOX Headset

Wide Range of available Options includes:

- External DC jack for Cigarette-Lighter adapter E-DC-5B or DC cable E-DC-6
- 6 X AA size Alkaline Battery Case FBA-25A

Actual Size

 **YAESU**
Choice of the World's Top DXersSM

FT-250R/E ULTRA-COMPACT 5 W 2 m FM HANDHELD TRANSCIVER

*E for European Version

Compact yet incredibly rugged, the FT-250R/E 2-meter handheld is designed to perform under the most difficult operating conditions. It is packed with the leading-edge features you've come to expect from a Yaesu product. The FT-250R/E's die-cast aluminum case houses a large, high-output speaker, and the illuminated keypad provides easy viewing during night time operation.

Main Features

- 209 Memory Channels with Alpha-numeric tags (maximum 7 characters)
- Direct Keypad Frequency Entry
- High Power Output: 5 Watts (FNB-83)
- Loud Audio 700 mW with the Internal Speaker
- Long life FNB-83 (7.2 V/ 1400 mAh) and Desktop Charger included
- CTCSS and DCS Encode/Decode, with split Tone and DCS Encode-only capability
- Scanning Mode: VFO / Memory / PMS / Dual Watch
- Nine DTMF Auto-dialer memories
- Keypad/Dial Lockout capability
- Two front panel programmable keys
- TX and RX Battery Savers
- Convenient Access key for the Vertex Standard's WIRES™ (Wide-coverage Internet Repeater Enhancement System)
- RF squelch (only pass signals exceeding the programmed level)
- Memory-only operating mode available
- Rugged and Water resistant case construction
- Smart Search Operation
- Battery Voltage Display
- Adjustable TX Deviation Level (± 5kHz or ± 2.5 kHz)
- Transmit Time-Out-Timer (TOT) and Automatic Power-Off (APO)
- Busy Channel Lock-Out (BCLO)
- Automatic Repeater Shift (ARS)
- ARTS™ (Auto-range Transponding System) which "beeps" the user when you move out of communication range

Technical specs subject to change without notice. The FT-250R has not been approved by the FCC. This device may not be sold or leased, or offered for sale or lease, until FCC approval has been obtained.

SPECIFICATIONS

General	
Frequency Ranges	RX 136 ~ 174 MHz TX 144 ~ 146 (148) MHz
Channel Steps	5, 10, 12.5, 15, 20, 25 and 50 kHz
Repeater Shift	±600 kHz
Emission Type	F2D, F3E
Antenna Impedance	50 Ohms
Supply Voltage	Nominal: 7.2 V DC, Negative Ground Operating: 6.0 ~ 16 VDC, Negative Ground (EXT DC JACK)
Current Consumption	130 mA (Receive) 37 mA (Standby, Saver Off) 23 mA (Standby, Saver On) 8 mA (Auto Power Off) 1.3 A (5 W TX 7.2 V DC)
Operating Temperature	-4° F to + 140° F (-20° C to + 60° C)
Case Size (W x H x D)	2.3" x 4.3" x 1.0" (58 x 108.5 x 26.5 mm) (w/o knob & antenna)
Weight	12.4 oz (352 g) with FNB-83, Antenna and Belt Clip
Transmitter	
RF Power Output	High 5 W (@ 7.2 V FNB-83) Mid 2 W (@ 7.2 V FNB-83) Low 0.5 W (@ 7.2 V FNB-83)
Modulation Type	Variable Reactance F2D, F3E
Maximum Deviation	±5 kHz F2D, F3E
Spurious Emission	At least 60 dB below (High & Mid)
Microphone Impedance	2 k Ohms
Receiver	
Circuit Type	Double-Conversion Super heterodyne
Intermediate Frequencies	1st: 21.7 MHz 2nd: 450 kHz
Sensitivity	0.16 µV for 12 dB SINAD
AF Output	700 mW @ 16 Ohms for 10 % THD (@7.4 V) Internal SP 400 mW @ 8 Ohms for 10 % THD (@7.4 V) EXT SP Jack

Specifications are subject to change without notice, and are guaranteed within the amateur bands only. Frequency ranges will vary according to transmitter version.

ACCESSORIES & OPTIONS

 MH-34B4B Speaker Microphone	 VC-25 VOX Headset	 VAC-10B/C/U* Desktop Charger (CD-30 and PA-38)	 E-DC-5B DC cable with Cigarette Lighter Adapter	 E-DC-6 DC cable; plug and wire only
 MH-37A4B Earpiece/microphone	 FNB-83 1400 mAh Ni-MH Battery	 FBA-25A Dry Cell Battery Case for 6 AA-size Alkaline cells	 CT-44 Microphone Adapter	 CN-3 BNC-to-SMA Adapter

About this brochure: we have made this brochure as comprehensive and factual as possible. We reserve the right, however, to make changes at any time in equipment, optional accessories, specifications, model numbers, and availability. Precise frequency range may be different in some countries. Some accessories shown herein may not be available in some countries. Some information may have been updated since the time of printing; please check with your Authorized Yaesu Dealer for complete details.



VERTEX STANDARD CO., LTD.

4-8-8 Nakameguro, Meguro-ku, Tokyo 153-8644, Japan

For the latest Yaesu news, visit us on the Internet: <http://www.vxstd.com>

VERTEX STANDARD <http://www.vertexstandard.com>

Phone +1 714-927-7600

US Headquarters
10900 Walker Street, Cypress, CA 90630, U.S.A.

<http://www.yaesu.co.uk>

YAESU UK LTD. Email: sales@yaesu.co.uk

Unit 12, Sun Valley Business Park, Winnall Close
Winchester, Hampshire, SO23 0LB, U.K.
Phone +44 196 286 6667

VERTEX STANDARD HK LTD. <http://www.vxstd.com.hk>

Unit 5, 20/F., Seaview Centre, 139-141 Hoi Bun Road,
Kwun Tong, Kowloon, Hong Kong
Phone +862 2732 2288



VERTEX STANDARD AUSTRALIA PTY. LTD.

Normanby Business Park, Unit 14/45 Normanby Road
Notting Hill 3168, Victoria, Australia
<http://www.vxstd.com.au>
Phone +61 3 95162100

2009.0505NA(U)/EXP(EU) B9200605 Printed in Japan